

SPEAKERS

Miniature



ELS20FL08G



ELS25FL08G



ELS27FL08G



ELS29FL08G



ELS29FL08LS



ELS38FL08G



ELS50CS08G

Model	Dimension Diameter x Depth ± 0.2mm	Impedance $\Omega \pm 15\%$	Power Rating		Fo Lowest Resonant Frequency Hz ± 150	SPL Sound Pressure Level db/W · M	Frequency Range SPL-10 db Hz.	Weight Grams
			Nor.	Max.				
ELS20FL08G	20 [∅] × 9.0	8	100	200	750	77	400~3500	7.4
ELS25FL08G	25 [∅] × 5.6	8	100	200	760	75	400~3500	6.0
ELS27FL08G	27 [∅] × 9.0	8	100	200	800	80	450~5000	7.6
ELS29FL08G	29 [∅] × 9.0	8	100	200	700	80	400~5000	8.0
ELS29FL08LS	29 [∅] × 6.0	8	100	200	750	80	400~6000	8.2
ELS38FL08G	38 [∅] × 8.5	8	100	200	550	80	300~3500	18.3
ELS50CS08G	50 [∅] × 8.0	8	200	400	330	84	150~3500	10.7

Low Profile Paper Cone



ELS38CP08



ELS40CP08



ELS45CP08



ELS50CP08



ELS57CP08

Model	Dimension Diameter x Depth ± 0.2mm	Impedance $\Omega \pm 15\%$	Power Rating		Fo Lowest Resonant Frequency Hz ± 150	SPL Sound Pressure Level db/W · M	Frequency Range SPL-10 db Hz.	Weight Grams
			Nor.	Max.				
ELS38CP08	38 [∅] × 8.2	8	250	500	640	82	300~3500	9.7
ELS40CP08	40 [∅] × 8.2	8	250	500	600	82	260~3500	10.7
ELS45CP08	45 [∅] × 8.3	8	250	500	550	85	270~6500	11.2
ELS50CP08	50 [∅] × 8.9	8	250	500	450	85	200~6000	13.0
ELS57CP08	57 [∅] × 9.6	8	300	500	430	85	200~3500	15.0

⊛ Impedance can be assigned by customers.