



# MOUNTING OPTIONS



**OPTION O**  
FOUR .125 DIAMETER  
NON-THREADED  
MOUNTING HOLES



**OPTION K**  
FOUR THREADED (4-40)  
MOUNTING HOLES



**OPTION N**  
FOUR GROUNDING BRACKETS  
(LOCKING TYPE)

MOUNTING OPTIONS	DESCRIPTION
<b>AO</b>	0.750" SPACING, WITH FOUR .125 DIAMETER NON-THREADED MOUNTING HOLES
<b>AOJ</b>	0.750" SPACING, WITH FOUR .125 DIAMETER NON-THREADED MOUNTING HOLES, AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTOR
<b>AK</b>	0.750" SPACING, WITH FOUR THREADED (4-40) MOUNTING HOLES
<b>AKJ</b>	0.750" SPACING, WITH FOUR THREADED (4-40) MOUNTING HOLES, AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>AN</b>	0.750" SPACING, WITH FOUR GROUNDING BRACKETS (LOCKING TYPE)
<b>ANJ</b>	0.750" SPACING, WITH FOUR GROUNDING BRACKETS (LOCKING TYPE), AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>BO</b>	0.900" SPACING, WITH FOUR .125 DIAMETER NON-THREADED MOUNTING HOLES
<b>BOJ</b>	0.900" SPACING, WITH FOUR .125 DIAMETER NON-THREADED MOUNTING HOLES, AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>BK</b>	0.900" SPACING, WITH FOUR THREADED (4-40) MOUNTING HOLES
<b>BKJ</b>	0.900" SPACING, WITH FOUR THREADED (4-40) MOUNTING HOLES, AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>BN</b>	0.900" SPACING, WITH FOUR GROUNDING BRACKETS (LOCKING TYPE)
<b>BNJ</b>	0.900" SPACING, WITH FOUR GROUNDING BRACKETS (LOCKING TYPE), AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>CO</b>	0.625" SPACING, WITH FOUR .125 DIAMETER NON-THREADED MOUNTING HOLES
<b>COJ</b>	0.625" SPACING, WITH FOUR .125 DIAMETER NON-THREADED MOUNTING HOLES, AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>CK</b>	0.625" SPACING, WITH FOUR THREADED (4-40) MOUNTING HOLES
<b>CKJ</b>	0.625" SPACING, WITH FOUR THREADED (4-40) MOUNTING HOLES, AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS
<b>CN</b>	0.625" SPACING, WITH FOUR GROUNDING BRACKETS (LOCKING TYPE)
<b>CNJ</b>	0.625" SPACING, WITH FOUR GROUNDING BRACKETS (LOCKING TYPE), AND WITH FOUR JACK SCREWS ASSEMBLED TO CONNECTORS