




# MOUNTING OPTIONS




**Option X**  
 .120 Diameter Holes




**Option K**  
 With #4-40 Threaded  
 Riveted Clinch Nuts




**Option J**  
 With #4-40 Threaded  
 Fixed Jack Screws



**Option KJ**  
 With #4-40 Threaded  
 Riveted Clinch Nuts  
 And Jack Screws  
 Assembled to Connector



**Option BR**  
 With #4-40 Threaded  
 Riveted Brackets



**Option BRJ**  
 With #4-40 Threaded  
 Riveted Bracket  
 And Jack Screws  
 Assembled to Connector

SERIES	MOUNTING OPTIONS
DDF	X, K, J, KJ, BR, BRJ (L = 8.50MM)
DDL	X, K, J, KJ, BR, BRJ (L = 14.50MM)
DSF	X, K, J, KJ
DCC	X, K, J, KJ
DS	X, K, J, KJ
DSH	X, K, J, KJ
DD	X, K, J, KJ, BR, BRJ (L = 6.00MM)
DDH	X, K, J, KJ, BR, BRJ (L = 6.00MM)
DDL	X, K, J, KJ, BR, BRJ (L = 11.00MM, 12.70MM)
DDLH	X, K, J, KJ, BR, BRJ (L = 9.65MM, 11.00MM, 12.70MM)
DC	X, K, J, KJ
DCH	X, K, J, KJ
DIDC	X, K, J, KJ
DMR	X, K, J, KJ
DMRM	X, K, J, KJ
DMRL	X, K, J, KJ