



# DDLH SERIES

D-SUB CONNECTOR  
HIGH DENSITY  
STRAIGHT PCB TYPE  
HIGH PROFILE



DDLH - E15SB - X - 000 ◀ EXAMPLE



## DIMENSIONS

SHELL SIZE	NO. OF CONTACT POSITIONS	A 0.010 0.25	B 0.005 0.13	C 0.015 0.38	D 0.010 0.25	E 0.010 0.25	F 0.005 0.13
E	15	0.643 16.33	0.984 24.99	1.213 30.81	0.759 19.28	0.277 7.04	0.090 2.29
A	26	0.971 24.66	1.312 33.32	1.541 39.14	1.083 27.51	0.271 6.88	0.090 2.29

To return to this page  
use return button in  
your browser

• MOUNTING OPTIONS:  
SEE PAGE 28

## HOW TO ORDER

SERIE	SHELL	PINS	M/F	MOUNTING OPTIONS	CONTACT PLATING	INSULATOR COLOR	SHELL FINISH
EXAMPLE → DDLH	E	15	SB	X	0	0	0
DDLH	E A	15 26	P SB	*X PAGE 28	*0 = G/F 4 = 15μ" 1 = SEL G/F 5 = 20μ" 2 = 5μ" 6 = 30μ" 3 = 10μ"	*0 = BLACK 1 = WHITE 2 = BLUE 3 = GRAY	*0 = TIN 1 = NICKEL 2 = ZINC 3 = ALL PLASTIC

\*STANDARD